



Classification: **A**



In accordance with standards EN 926-1:2015, EN 926-2:2013 and LTF NFL II-91/09:

PG_1592.2019

Date of issue (DMY):

01.10.2019

Manufacturer:

Niviuk Gliders / Air Games S.L.

Model:

Koyot 4 P 24

Serial number:

OIKT4242V1

Configuration during flight tests

Paraglider

Maximum weight in flight (kg)	80
Minimum weight in flight (kg)	60
Glider's weight (kg)	3.5
Number of risers	3
Projected area (m2)	20.45

Accessories

Range of speed system (cm)	13
Speed range using brakes (km/h)	15
Total speed range with accessories (km/h)	21
Range of trimmers (cm)	0

Harness used for testing (max weight)

Harness type	ABS
Harness brand	Advance
Harness model	Success 4 M
Harness to risers distance (cm)	44
Distance between risers (cm)	40

Inspections (whichever happens first)

every 24 months or every 100 flying hours
Warning! Before use refer to user's manual
Person or company having presented the glider for testing: **None**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A 0



Classification: **A**



In accordance with standards EN 926-1:2015, EN 926-2:2013 and LTF NFL II-91/09:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

PG_1593.2019

01.10.2019

Niviuk Gliders / Air Games S.L.

Koyot 4 P 26

OIKT4P262V1

Configuration during flight tests

Paraglider

Maximum weight in flight (kg)	95
Minimum weight in flight (kg)	75
Glider's weight (kg)	3.9
Number of risers	3
Projected area (m2)	22.16

Accessories

Range of speed system (cm)	15
Speed range using brakes (km/h)	15
Total speed range with accessories (km/h)	21
Range of trimmers (cm)	0

Harness used for testing (max weight)

Harness type	ABS
Harness brand	Supair
Harness model	Evo XC 3 L

Inspections (whichever happens first)

every 24 months or every 100 flying hours
Warning! Before use refer to user's manual
Person or company having presented the glider for testing: None

Harness to risers distance (cm) **44**

Distance between risers (cm) **44**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A 0



Classification: **A**



In accordance with standards EN 926-1:2015, EN 926-2:2013 and LTF NFL II-91/09:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

PG_1594.2019

01.10.2019

Niviuk Gliders / Air Games S.L.

Koyot 4 P 28

OIKT4282V1

Configuration during flight tests

Paraglider

Maximum weight in flight (kg)	115
Minimum weight in flight (kg)	90
Glider's weight (kg)	4.1
Number of risers	3
Projected area (m2)	23.86

Accessories

Range of speed system (cm)	13
Speed range using brakes (km/h)	15
Total speed range with accessories (km/h)	21
Range of trimmers (cm)	0

Harness used for testing (max weight)

Harness type	ABS
Harness brand	Supair
Harness model	Evo XC 3 L

Inspections (whichever happens first)

every 24 months or every 100 flying hours
Warning! Before use refer to user's manual
Person or company having presented the glider for testing: **None**

Harness to risers distance (cm) **44**

Distance between risers (cm) **48**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A 0