


FTR - Flight Test Report

Dieser Prüfbericht darf ohne schriftliche Zustimmung der EAPR nicht, auch nicht auszugsweise, vervielfältigt werden.

Manufacturer	 AIRDESIGN GmbH Röhrenbergstraße 9 A-6967 Absam	Type testing No.	EAPR-GS-0845/18
		serial number	Proto
Model	Susi 3,23	Location	Achensee Rofan, Achensee



Rev. 2,3 - 26.11.2014
 EAPR GmbH - Marktstr. 11
 D-87730 Bad Grönenbach - Germany

Date of testing	03.05.2018	Minimum take off weight 72 kg	Maximum take off weight 122 kg
Testpilot	Mike Küng		Anselm Rauh
Harness	Eapr-Testequipment		EAPR
Pilot's take off weight	72 kg		122 kg

Classification	B
----------------	----------



Test-criteria	Minimum take off weight	Evaluation	Maximum take off weight	Evaluation
1. Inflation / take-off - 4.4.1				
Rising behavior	Smooth, easy and constant rising, no pilot correction required	A	Smooth, easy and constant rising, no pilot correction required	A
Special take off technique required	No	A	No	A
2. Landing - 4.4.2				
Special landing technique required	No	A	No	A
3. Speeds in straight flight - 4.4.3				
Trim speed more than 30km/h	Yes	A	Yes	A
Speed range using the controls larger than 10km/h	Yes	A	Yes	A
Minimum speed	Less than 25 km/h	A	25 km/h to 30 km/h	B
4. Control movement - 4.4.4				
Max. weight in flight up to 80kg		-		-
Max. weight in flight 80 to 100kg	Increasing > 60cm	A		-
Max. weight in flight greater than 100kg		-	Increasing >65 cm	A
5. Pitch stability exiting accelerated flight - 4.4.5				
Dive forward angle on exit	Dive forward less than 30°	A	Dive forward less than 30°	A
Collapse occurs	No	A	No	A
6. Pitch stability operating controls during accelerated flight - 4.4.6				
Collapse occurs	No	A	No	A
7. Roll stability and damping - 4.4.7				
Oscillations	Reducing	A	Reducing	A
8. Stability in gentle spirals - 4.4.8				
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
9. Behaviour exiting a fully developed spiral dive - 4.4.9				
Initial response of glider (first 180°)	No immediate reaction	B	No immediate reaction	B
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
Turn angle to recover normal flight	720° to 1080°, spontaneous recovery	B	720° to 1080°, spontaneous recovery	B
10. Symmetric front collapse - 4.4.10				
Folding lines used	No		No	
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	0° - 30° Entering a turn of less than 90°	A	0° - 30° Keeping course	A
Cascade occurs	No	A	No	A
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	30° - 60° Entering a turn of less than 90°	B	0° - 30° Keeping course	A
Cascade occurs	No	A	No	A
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	30° - 60° Entering a turn of less than 90°	B	0° - 30° Keeping course	A
Cascade occurs	No	A	No	A
11. Exiting deep stall (parachutal stall) - 4.4.11				
Deep stall achieved	Yes		Yes	
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	30° - 60°	B	30° - 60°	B
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	A	No	A

12. High angle of attack recovery - 4.4.12											
Recovery	Spontaneous in less than 3 sec				A	Spontaneous in less than 3 sec				A	
Cascade occurs	No				A	No				A	
13. Recovery from a developed full stall - 4.4.13											
Dive forward angle on exit	30° - 60°				B	30° - 60°				B	
Collapse	No collapse				A	No collapse				A	
Cascade occurs (other than collapse)	No				A	No				A	
Rocking backward	Less than 45°				A	Less than 45°				A	
Line tension	Most lines tight				A	Most lines tight				A	
14. Asymmetric collapse (trim speed) - 4.4.14											
Folding lines used	No					No					
Change of course until re-inflation	trim speed, max 50% collapse	< 90°	Dive or roll angle	15° - 45°	A	< 90°	Dive or roll angle	15° - 45°	A		
Re-inflation behavior		Spontaneous re-inflation				A	Spontaneous re-inflation				A
Total change of course		Less than 360°				A	Less than 360°				A
Collapse on the opposite side occurs		No				A	No				A
Twist occurs		No				A	No				A
Cascade occurs	No				A	No				A	
Change of course until re-inflation	trim speed, max 75% collapse	90° - 180°	Dive or roll angle	15° - 45°	B	90° - 180°	Dive or roll angle	15° - 45°	B		
Re-inflation behavior		Spontaneous re-inflation				A	Spontaneous re-inflation				A
Total change of course		Less than 360°				A	Less than 360°				A
Collapse on the opposite side occurs		No				A	No				A
Twist occurs		No				A	No				A
Cascade occurs	No				A	No				A	
Change of course until re-inflation	accelerated, max 50% collapse	< 90°	Dive or roll angle	15° - 45°	A	< 90°	Dive or roll angle	15° - 45°	A		
Re-inflation behavior		Spontaneous re-inflation				A	Spontaneous re-inflation				A
Total change of course		Less than 360°				A	Less than 360°				A
Collapse on the opposite side occurs		No				A	No				A
Twist occurs		No				A	No				A
Cascade occurs	No				A	No				A	
Change of course until re-inflation	accelerated, max 75% collapse	90° - 180°	Dive or roll angle	15° - 45°	B	90° - 180°	Dive or roll angle	15° - 45°	B		
Re-inflation behavior		Spontaneous re-inflation				A	Spontaneous re-inflation				A
Total change of course		Less than 360°				A	Less than 360°				A
Collapse on the opposite side occurs		No				A	No				A
Twist occurs		No				A	No				A
Cascade occurs	No				A	No				A	
15. Directional control with a maintained asymmetric collapse - 4.4.15											
Able to keep course straight	Yes				A	Yes				A	
180° turn away from the collapsed side possible in 10 sec	Yes				A	Yes				A	
Amount of control range between turn and stall or spin	More than 50% of the symmetric control travel				A	More than 50% of the symmetric control travel				A	
16. Trim speed spin tendency - 4.4.16											
Spin occurs	No				A	No				A	
17. Low speed spin tendency - 4.4.17											
Spin occurs	No				A	No				A	
18. Recovery from a developed spin - 4.4.18											
Spin rotation angle after release	Stops spinning in less than 90°				A	Stops spinning in less than 90°				A	
Cascade occurs	No				A	No				A	
19. B-line-stall - 4.4.19											
Change of course before release	Changing course less than 45°				A	Changing course less than 45°				A	
Behaviour before release	Remains stable with straight span				A	Remains stable with straight span				A	
Recovery	Spontaneous in less than 3 sec				A	Spontaneous in less than 3 sec				A	
Dive forward angle on exit	30° - 60°				A	0° - 30°				A	
Cascade occurs	No				A	No				A	
20. Big ears - 4.4.20											
Entry procedure	Standard technique				A	Special device required				A	
Behaviour during big ears	Stable flight				A	Stable flight				A	
Recovery	Spontaneous in less than 3 sec				A	Spontaneous in less than 3 sec				A	
Dive forward angle on exit	0° - 30°				A	0° bis 30°				A	
21. Big Ears in accelerated flight - 4.4.21											
Entry procedure	Standard technique				A	Special device required				A	
Behaviour during big ears	Stable flight				A	Stable flight				A	
Recovery	Spontaneous in less than 3 sec				A	Spontaneous in less than 3 sec				A	
Dive forward angle on exit	0° - 30°				A	0° bis 30°				A	
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight				A	Stable flight				A	
23. Alternative means of directional control - 4.4.22											
180° turn achievable in 20 sec	Yes				A	Yes				A	
Stall or spin occurs	No				A	No				A	
23. Any other flight procedure and/or configuration described in the user's manual - 4.4.23											
Procedure works as described					NA					NA	
Procedure suitable for novice pilots					NA					NA	
Cascade occurs					NA					NA	
24. Remarks of testpilot:											