



Manual Student NG



Owner's manual 18.10.2010

Paragliding Harness

With the Student you got one of the most comfortable and most functional harnesses, which is available on the market at present. We thank you for the confidence, for buying the Student harness.

Please read this operating instructions carefully and consider, that AVA Sport Ltd. can not be made liable for accidents and damage, which result from disregarding of the operating instructions.

- Running through shoulder belts for perfect comfort
- Weight of the harness: 3.6 kg (M)
- ✓ Seatposition adjustable in flight

✓ Overview:

- a) Lateral chest-belt adjustment
- b) Leg belts with combi-safety-system
- c) speed-bar
- d) Main suspension
- e) Rescue system release-handle



1. Adjustment possibilities:

By the versatile adjusting possibilities of the Student we recommend in any case that all adjustments are done in a simulator before the first flight to guarantee an optimal seat comfort.

Adjusting the leg belts:

When you put the harness on, please take care that the buckles are closed correctly and audibly. The leg belts should be fastened tight but should leave still enough space, for the starting and landing phase, where the legs should have still some space to move.

Speed-bar:

The speed-bar is generally built in and runs from the risers as follows: rear pulley-roll, then to the frontal pulley at the seat-board.



2. Build-in of the rescue-system



Connection to the Handle



Connection to the Harness




Put the bridle into the container of the hanrness. The connection to the handle must be also between the inner-container and the harness, as shown on the picture. That means it has to be on the inner side. So you can be sure that the rescue-system can be pulled out easily.



Put in the rescue-system container. The connected handle is showing to the seatboard and the container opening of the harness



The connection to the handle runs between the two upper eyes. You have to take care that the connection of the handle is not hindered in any way and is still long enough, so that you can be sure that the pull is coming first on the closing-pins and not on the connection to the inner container!



Line must be free be moved



Close the container with two packing cords. Order:



After closing the container, by putting in the pins, remove the packing cords and put the release-handle in the therefore assigned pockets







Attention:

After every installation of a rescue-system in a harness there must be a test if the opening force is between 2 and 5 daN. If harness and rescue parachute are combined the first time a compatibility check have to be done by a authorized person!

Back-protector:

Only the original back-protecor which is inside the Student is allowed to use.

Usage:

The protector should protect the pilot's back in case of a unintentional hard landing.

Description:

The protector exists of a shock absorbing special softfoam. Both together are absorbing the energy of a hard impact.

Function:

On a impact of the pilot the protector gets compressed and absorbs so the energy of the impact. This minimizes the probability of serious spine injuries but does not except it. Because the protector is very flexible you don't have to make any adjustments at the protector itself.

On waterlandings you should get rid of the harness as soon as possible, because the buoyanzy of the protector may turn the pilot upside down and pushes him under the water surface.

There are no special restrictions concerning towing&winching.

In cases of emergency it's important that the pilot absorbs the impact with a little bit bended knees, because so the human body can stand 4-6 times higher impact-forces. If the pilot tries to compensate the impact with straight knees the complete energy is coming directly on the pilot's spine, so the protector can not work efficient or begins it's compensating to late.

Maintenance/Duration of life:

The protector is maintenance free and can still be used after an impact, if you can not see any damages! But anyway avoid high temperatures (for example in the car) and contact with corrosive or etching substances. If, what normally is not necessary, the protector needs to be cleaned, just use water and soft soap.

The provisional duration of life are 5 years. Please give us a call after this 5 years, because then we have checked even older protectors' function and performance, and can decide over a longer duration of life. (What most probably will not be a problem).

Tandem flights:

The Student can be used without Resque as passenger's Harness bud not as Pilots Harness

Life span, replacing time of construction units, repair hints:

The harness Student was built for high loads and strong use. Accordingly, for the choice of the materials particularly high criteria were set. However the life span depends also on the treatment of the harness by the pilot, so we recommend to check the harness from time to time, if there are faulty or damaged parts, which should be replaced or repaired then.

Especially take care of defective seams, which should be immediately repaired by an authorized workshop. Further you have the possiblity to send us the harness for checking.

In order to prevent problems with the harness we recommend:

- avoid handling with fire and sharp edged articles near your harness.
- avoid unnecessarily long sun effect, because ultraviolet radiation destroys the molecular structure of the material
- avoid the contact with seawater or acid liquids.

Maintenance and control:

The harness Student is more or less maintenance-free. But regular control in short periods gives you the guarantee of an unrestricted function of your belt system. Take particularly care that the buckles stay free of dirt.

Dealers:

AVA Sport Switzerland:

Flugsau GmbH, Gruobi 1, 6388 Grafenort, www.avasportcentral.ch

AVA Sport Germany / Austria:

Bernd Hornböck, Görtschach 40, 9170 Ferlach bernd@aigainstthegrain.at

AVA Sport France:

Parapente Passion - 14 Rue Basse - 04500 Riez www.avasport.fr

Certification Student NG

ISO 9001 BUREAU VERITAS Certification	Parag	liding harne Student	ss / Gurtzeug NG				
Test reference-No / Prüf-Nr		GZ 012.2010		Integrated Parachute Cont: Integr. RG-Cont:		Ja-Yes	
Manufacturer / Hersteller		AVA Sports Ltd.			Periodic Inspection After: Regelmässige Nachprüfung Nach:		
Maxi Load / Max Anhängelast		20 kg]		
Conformtity Checked By: Stückeprüft Durch:			Monat / Jahr : Month / Year :				
Certifcation Date / Prüfun		Conform	nity tests according to <u>2.</u> Angewandte	Vor Gebraud DV LuftGerPV \$1, Nr. Prüfrichtilinien / Norm) Pré-au-Comte 8 CH 121 965 65 65 mobile	lesen! Air Turquaise SA 1-1844 Villeneuve	

ISO 9001	Paragliding harness / Gurtzeug für Gleitschirm						
BUREAU VERITAS Certification	Student NG						
Test reference-No / Prüf-Nr	PH 012.2010)		Integrated Parachute Cont: Integr. RG-Cont:	yes		
Manufacturer / Hersteller	AVA Sports Ltd.	AVA Sports Ltd.			:		
Maxi Load / Max Anhängelast	120 kg						
		_					
Conformtity Checked By: Stückeprüft Durch:		Monat / Jahr : Month / Year :					
Certifcation Date / Prüfung Datum	21.10.2010	1	Before	Before use referto the user's manual!			
, ,			Vor Ge	Vor Gebrauch Betriebsanweisung lesen!			
para-test.co	m Propa	Conformity tests accor Angewan	dte Prüfrichtilinien	999 standards carried out by: Normen durch:	Air Turquoise SA 1-1844 Villeneuve		

paragliding by air furquoise

tel. +41 21 965 65 65 | mobile +41 79 202 52 30

info@para-test.com