Welcome to ADVANCE

Many thanks for choosing the STRAPLESS 2, an ADVANCE high-quality ultralight product. We wish you plenty of fun and many enjoyable hours in the air with it

This Getting Started is both guide and manual in one, and therefore forms animportant part of your flying equipment.

Here you will find not just instructions for setting up and use in practice, but also important advice about safety, care and maintenance. We therefore advise you to carefully read it through before your first STRAPLESS 2 flight.

Register your product on www.advance.ch/warranty,

so that you will receive information about product updates and safety relevant matters about the STRAPLESS 2, direct from us

Important notice

The STRAPLESS 2 is certified according to DIN EN 1651 for a maximum pilot weight of 110 kg (load test only).

Due to its ultra light construction, it is completely forbidden to carry out acro or extreme flight manoeuvres, including the taking part in safety training (SIV) and winching! Every pilot carries sole responsibility for all risks associated with paragliding, including injury and death. Neither the manufacturer nor the seller of paragliding equipment can guarantee the safety of the pilot or be held responsible for it.

Handle with care

The STRAPLESS 2 is extremely light and intended for a specific use. The choice of materials and design make the harness sensitive to damage caused by inappropriate handling. The "Handle with Care" label should always be borne in mind – the lifespan of this product very much depends on your awareness and consideration.

The following actions can significantly reduce the life of your STRAPLESS 2:

- Speed-Flying and Speed-Riding
- (Coast) Soaring with permanent touch & go
- · Extensive Ground-Handling

The GRIVEL PLUME alu-screw-carabiner is an ultralight product (37 gm, 22 kN) and requires special care:

- Do not use the carabiner if visible external damage is evident, or signs of wear appear.
- Avoid side loading, needless dropping and impact.
- The alu-carabiners should be changed after 3 years or 300 flights.



Delivery & Options

Before delivery every ADVANCE product has to be checked by the dealer for completeness of the delivery package and correct basic settings.

The STRAPLESS 2 delivery package contains:

- Harness
- Two GRIVEL PLUME carabiners
- Pack bag

Optional STRAPLESS 2 extras:

- Speedkit
- ADVANCE ZIP LIGHT front container for a reserve
- PIPACK RUCKSACK with 31 or 37 litres volume






Features

The STRAPLESS 2 weighs only 195 grams and is aimed at hikers and mountaineers who make no compromises in terms of weight and volume. The STRAPLESS 2 has now lightweight adjustable shoulder straps.

- 1 Lightweight adjustable shoulder straps
- 2 Chest strap closure system
- 3 EASY CONNECT LIGHT SYSTEM
- 4 GRIVEL PLUME alu screw carabiners
- 5 Bullet-Toggle, can be opened for more freedom of leg movement
- 6 Four loops for fastening the optional speedkit low-friction-rings



Fixing the Speedkit

An optional Speedkit is available for the STRAPLESS 2, with which an accelerator can be attached. The Speedkit comes with four low-friction rings and an accelerator cord


Pass one of the four white line loops on each side of the STRAPLESS 2 through the low-friction ring and then put the line loop over it.

Then guide the accelerator through the low-friction rings.

Attention: Never guide the accelerator directly through the line loops on the sides of the STRAPLESS 2.

Risk of damage due to friction!





Get into the harness

Put on & close harness

The shoulder straps allow you to put on the STRAPLESS 2 like a normal harness. To close the harness, hook the red and blue loops of the chest strap into the main carabiners. Please check that the carabiners and the other loops are not twisted.

Adjust shoulder straps

Adjust the length of the shoulder straps of your STRAPLESS 2 to your body size before the first flight. To adjust the length, move the position of the single knot above the large red end knot.

Get into the harness with a paraglider attached

If you store your harness connected to the paraglider, e.g. because you use soft links, you have to enter with your feet first from above through the closed locking system. Please be aware to not damage the harness with your shoes (e.g. with crampons).





Fixing a front reserve

The STRAPLESS 2 can be used with a front container (e.g. ZIP LIGHT). Hang the ends of the reserve connection in the carabiners. Then fasten the container as recommended by the manufacturer. The ZIP front container can be hung in the STRAPLESS 2 carabiners when the lines from the Y-connections are fixed to carry the weight of the reserve.

Important advice for using a front container


The STRAPLESS 2 carabiner gates must face rearwards. This is essential so that when the reserve is thrown the reserve connections run upwards unimpeded. In addition the reserve must be hung in the carabiners before hooking up the paraglider risers.



Attaching the paraglider risers

The STRAPLESS 2 has an EASY CONNECT LIGHT SYSTEM. The red and blue markings on the hangpoints simplifies clipping an ADVANCE paraglider in.

Attention: Make sure that you screw the carabiner gate locks fully home, and that the carabiners are only loaded in their lengthwise direction.



Warranty & Service

Set up a MyADVANCE-Account on www.advance.ch/warranty and register your STRAPLESS 2 direct online after purchase. You will then benefit from the extended ADVANCE warranty. This includes an extension of the legal warranty obligation of your country by one year.

Your STRAPLESS 2 must have a check every 24 months and be regularly inspected. Damage must be immediately rectified by an authorised service station. In addition, the GRIVEL PLUME alu-screwcarabiner should be changed after 3 years or 300 flights.

More detailed information about the worldwide ADVANCE Service Network can be found on www.advance.ch.
There you can also find advice about safety and up-to-date messages, as well as answers to FAQs.



advance thun ag uttigenstrasse 87 ch 3600 thun

VDAVACE



Getting Started